

# DURAIPOS®



DPT 100



- Triple interface
- Easy paper loading
- 300mm/s high printing speed
- 2 Year SWAP warranty

# DURAPOS®

Specifications	Description	
<b>Print</b>	Printing method Effective Printing Width Resolution Printing Speed Printing Density Character Set Print Font  Character per Line  Line space	Thermal line 72mm or 64mm 203dpi (8 dot/mm) 300mm/S 504dot/line or 576dot/line ANK,GB18030(Chinese) ASCII Font A : 12×24 ASCII Font B : 9×24 Chinese: 24×24 Font A-42line or 48line/Font B-56line or 64line/Simplified, complex font-21line or 24line 3.75mm (available command to adjust line space)
<b>Paper Spec</b>	Paper Width Paper Roll Diameter Paper supply method	79.5±0.5mm Φ80mm easy paper loading
<b>Barcodes</b>	Barcodes type Extended character table	UPC-A,UPC-C,EAN-13,EAN-8,CODE39,ITF,CODEBAR,CODE93,CODE128 PC437, Katakana, PC850, PC860, PC863, PC865, WPC1252, PC866, PC852, PC858
<b>Reliability</b>	MCBF TPH Auto cutter	60 million lines 100 million pulses (100KM) 1,000,000 cuts
<b>Interface</b>	DPT100-URE DPT100-URW	Serial+Ethernet+USB WIFI+Serial+USB
<b>Paper near end sensor</b>		Yes
<b>Printing command</b>		ESC POS / OPOS
<b>System supported</b>		Windows / OPOS / Linux / Android / IOS
<b>Power Supply(Adapter)</b>		DC 24V,2.5A
<b>Standard supplied in box</b>		Power supply / USB cable / Serial cable / Drivers / paper roll
<b>Printer Dimesion (L × W × H )</b>		200×145×142mm
<b>Environment</b>		Operating : 0~45°C Stock : -10~50°C

