

# DURAMOS®



DPT 200



- Triple interface
- Supports top or front loading paper
- 260mm/s high printing speed
- 2 Year SWAP warranty

# DURAPOS®

Specifications		Description
<b>Print</b>	Printing method Resolution Printing Speed Printing width	Direct thermal line printing Standard 203dpi (8 dots/mm) / Standard 180dpi (7 dots/mm) Max. 260mm/s 72mm
<b>Interface</b>	Standard	USB + Serial + Ethernet
<b>Page mode</b>		Support
<b>Barcode</b>	1D 2D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93 PDF417, QR code
<b>Fonts</b>	Chinese Alphanumeric User-defined Codepage	GBK 24x24 dots ASCII 9x17, 12x24 dots Yes 48
<b>Memory</b>	RAM Flash	32MB 64MB
<b>Graphics</b>		Support bitmap printing with different density and user defined bitmap printing.
<b>Detection</b>	Sensors	Paper out and paper near end sensors, cover open switch
<b>LED indicator</b>	Paper Power Error	Blue LED Orange LED Red LED
<b>Reliability</b>	TPH life Cutter life	150KM 2 million cuts
<b>Power supply</b>	Input Output	AC 100v – 240v DC 24V/2.5A
<b>Paper</b>	Paper type Paper width Paper thickness Roll paper diameter Paper load Paper cut	Thermal receipt printer 58mm / 80mm 0.056/80mm max. OD Ø83mm Front or top paper loading Partial cut or full cut
<b>Environment</b>	Operation Storage	0°C ~ 45°C, 25% ~ 85%RH -30°C ~ 60°C, 5% ~ 95%RH Physical
<b>Physical Characteristics</b>	Dimension Weight	134.8(L)x132(W)x132(H)mm 1.37KG(without paper roll)
<b>Options &amp; Accessories</b>		USB/serial cable, paper roll, power adapter, power cord, CD, quick start guide
<b>Software</b>	Emulation  Driver	ESC/POS Windows2000/ XP / Win7/Win8/Win10/POSReady/Linux/OPOS
	SDK	WinCE, Win Mobile, Android, iOS



Retail



Horeca



Grocery



Entertainment