

The Anybus Edge Gateway family makes sure to bring data from the factory floor through the edge, properly analyzed and packaged, to the cloud. The event driven data flow makes the product not only perfect for monitoring applications, but also for enabling the IoT systems to get control. With the Edge Gateways, you have the possibility to access data remotely and securely while also allowing for full remote device management.



### SYSTEM OVERVIEW



### Protocols supported:

Modbus RTU Master/Slave  
Modbus TCP Master/Slave  
PROFIBUS Slave  
PROFINET Slave  
EtherNet/IP Adapter/Slave  
M-Bus Master  
Digital I/O  
Analog/Digital I/O  
Analog/Digital/RTD I/O  
OPC UA Server  
MQTT Client

### Features and benefits

- HMS Hub connectivity
- Enable easy remote control and management
- Provide Modbus-TCP client/server and Modbus-RTU master/slave interfaces
- Enable OPC UA, MQTT, SNMP, SNTP
- Provide I/O, M-Bus, PROFIBUS, PROFINET and EtherNet/IP interfaces
- WLAN/UMTS support
- Powerful graphical edge intelligence design tool
- Simple web configuration interface
- Firewall, OpenVPN & password protection
- NAT routing
- Root user authentication
- TLS data encryption
- HTTPS port usage
- Device initiated connections
- Central or local device management
- Mass deployable updates
- Real-time status information
- Alerts and automatic responses

### Ease of use

The Anybus Edge Gateways are built for ease of use. They feature HMS Sequence, a powerful graphical programming tool to build your needed edge intelligence. Configuration and deployment can be done locally or remotely via a simple web interface.

### Security and device management

Security and proper device management are important cornerstones for your edge eco system. The Anybus Edge Gateways keeps your data properly encrypted and enable devices to stay updated and ready for future threats, in real time.



HMS provides a full 3 year product guarantee

## Technical Specifications

Software		
Operating System	IPC@CHIP® RTOS-LNX Real-time operating system	
HMS Sequence editor and runtime	Visual programming editor running on the internal web server - I/O mapping editor - Up to 8192 I/O values - Up to 1024 portal variables	
Technical Details		Standard
Dimensions (L•W•H)	100 series: 79 x 46 x 107 mm 140 series: 79 x 65 x 107 mm	
Protection class	IP20, NEMA rating 1	IEC 60529
Enclosure material	Continuously hot-dip aluminium-zinc coated steel	
Installation position	Vertical position	
Mounting	DIN rail (35•7,5/15)	EN 50022
Certifications		
UL	File number: Pending	UL 508 Ind. Cont. Eq.
CE	2014/30/EU (EMC)	IEC 61000-6-3 IEC 61000-6-2 IEC 62368-1
Electrical Characteristics		
Power	24 VDC, BL 3.50/03 connector	
Current consumption	< 0.2 A	
Hardware Characteristics		
Reverse voltage protection	Yes	
Short circuit protection	Yes	
Environmental Characteristics		
Operating temp	0 to +55 °C (+32 to +131 °F)	
Storage temp	-20 °C to +60 °C	
Relative Humidity	5% to 85% relative humidity, non-condensing	
Immunity and Emission for Industrial Environment		
Electrostatic discharge	+4kV contact, +8kV air	EN 61000-4-2
Electromagnetic RF fields	10 V/m 80 MHz - 1 GHz 3 V/m 1,4 GHz - 2,0 GHz 1 V/m 2,0 GHz - 2,7 GHz	EN 61000-4-3
Fast Transients	+2KV DC, +- 1KV signal	EN 61000-4-4
Surge protection	+/- 0.5kV CM / +-1kV DM on DC, +1kV signal	EN 61000-4-5
RF conducted interference	10 V/rms	EN 61000-4-6
Emission (at 3 m)	0.15 MHz – 0.5Mhz 40-30dBµA/m (QP) 30-20dBµA/m (Avg)  0.5 MHz – 30Mhz 30dBµA/m (QP) 20dBµA/m (Avg)	EN 55016-2-3
Single Pack Accessories		
• Installation sheet		

## INTERFACE FEATURES

1 = Network connector, 2 = Baud rate,  
3 = I/O data, 4 = Other, 5 = Amount of slaves / adapters

Basic Communsication	
<b>Ethernet Port</b>	1 = RJ45 2 = 10/100 Mbit/s
<b>Modbus TCP</b>	3 = 4096 values (up to 8192 values including array members) 4 = Modbus TCP client/server 5 = Up to 128 devices
<b>OPC UA Server</b>	3 = 4096 values (up to 8192 values including array members)
<b>MQTT Client</b>	4 = MQTT Client Only Implementation
<b>COM Serial Port</b>	1 = BL 3.50/08 connector 2 = 300bps-187,5kbps 4 = COM server specification according to RFC 2217
<b>Modbus RTU</b>	3 = 4096 values (up to 8192 values including array members) 4 = Modbus RTU master/slave 5 = Up to 128 devices

### Extra OT communication variations

<b>PROFIBUS Slave</b>	1 = D-Sub9 2 = Up to 12 Mbit/s 3 = Max 244 bytes IN/OUT 4 = Profibus DP (IEC 61158)
<b>PROFINET I/O Slave</b> <b>PROFINET IRT Slave</b>	1 = 2 x RJ45 2 = 100 Mbit/s fixed 3 = Max 1440 byte IN/OUT 4 = RT Communication and integrated IRT switch functionality. Support for MRP (Media Redundancy Protocol). RT Communication and integrated IRT switch functionality. Support for MRP (Media Redundancy Protocol)
<b>EtherNet/IP Slave</b>	1 = 2 x RJ45 2 = 10/100 Mbit/s 3 = Max 1448 byte IN/OUT 4 = Support for DLR (Device Level Ring Beacon-based)
<b>M-Bus Master</b>	1 = BL 3.50/10 connector 2 = 300 - 9600 bit/s 3 = 4096 values 5 = Up to 64 devices
<b>Digital I/O</b>	1 = BL 3.50/10 connector 3 = 4 x digital inputs/4 x digital outputs
<b>Analog/Digital I/O</b>	1 = BL 3.50/10 connector 4 = Digital input/output: 8 x digital inputs/outputs Analogue input: 8 x analogue inputs (voltage or current)
<b>Analog/Digital/RTD I/O</b>	1 = BL 3.50/10 connector 4 = Digital input/output: 4 x digital inputs/outputs Analogue input/output: 4 x analogue inputs (voltage or current), 2 x analogue outputs (0 – 10 V, 10 mA (nom)) RTP input/output: 2 x resistance thermometers inputs (2-wire), PT100 / PT500 / PT1000

### Wireless Connection

<b>UMTS</b>	1 = SMA Female 4 = GSM/GPRS Quad band: 850/900/1800/1900 MHz, UMTS Seven band: 800/850/900/AWS 1700/1900/2100 MHz, MiniSIM (2FF)
<b>WLAN</b>	1 = SMA Female 4 = IEEE 802.11 a/b/g/n, Dual band (2.4GHz, 5GHz), WPA/WPA2-PSK

