

Link/2500

Smart, sleek, simple.
Payment excellence at its finest.

- Specifically engineered for flexibility to accept all payment methods including NFC/Contactless, Apple Pay and Samsung Pay
- Optimize your payment solution for any existing infrastructure thanks to a fully versatile connectivity options
- Payment acceptance in your pocket! The ideal payment terminal for busy mobile merchants.



smartcard



magstripe



contactless



touchscreen




color display



speaker



connectivity



TELIUM
TETRA

■ With the Link/2500, Ingenico brings payment acceptance solution to any mobile business.

Highest security

The Link/2500 is PCI-PTS 5.x certified. Its Telium Tetra OS uses the latest cryptographic schemes with future-proof key length.

All payment options

In addition to EMV Chip & PIN, swipe and sign, Link/2500 supports the broadest range of contactless standards allowing NFC couponing and wallet use cases.

Maximized network availability

In one single terminal, Link/2500 proposes a full spectrum wireless connectivity (3G, fallback GPRS, Dual SIM, Bluetooth and WiFi), offering flexibility to mobile merchant, while optimizing communication costs.

Designed for accessibility

Thanks to an integrated speaker which could provide vocal assistance and a real mechanical keypad with raised marking, Link/2500 is built for the most demanding use.

Designed for mobility

Featuring a pocket-sized, light weight and robust design the Link/2500 is the perfect business acceptance point for mobile merchants.

User-friendly and intuitive interface

Featuring an edge design, Link/2500 is user oriented featuring thanks to a bright 2.4" color display touchscreen capability and a USB-C connector which can be plugged upside down.

Secure Telium TETRA OS

Backed by 30 years of experience and with its user-friendly interface, the Telium TETRA operating system includes the best security mechanisms embedded to protect transaction privacy and leverages Ingenico's unique portfolio of payment applications.

Digital receipt management

Link/2500 minimizes environmental footprint thanks to its paperless approach enabled by digital receipt while reducing the Total Cost of Ownership.



NAME			Link/2500	Link/2500 Touch
Processor	Crypto and Applications processor	Cortex A5	●	●
Memory	Internal	256 MB Flash, 128 MB RAM 126 MB Flash, 128 MB RAM	●	●
OS		Telium TETRA	●	●
SIM / SAM		Up to 2	Option	
Card readers	Smart card	EMV Level 1, 50K lifespan	●	●
	Magstripe	ISO1/2/3, 100K lifespan	●	●
	Contactless	EMV / ISO14443	Option	Option
Display	Size	2.4" colour display, backlit, QVGA (240 x 320 pixels)	●	●
	Capacitive touchscreen		N/A	●
Keypad	Mechanical	20 keys, raised marking Backlighting keypad	●	Option
Audio	Buzzer		●	●
	Speaker		Option	Option
Terminal connectivity	WAN	3G (Fallback GPRS) ; Dual SIM	Option	Option
	LAN	Bluetooth WiFi (Dual band)	Option Option	Option Option
	Apple IAP Chip		Option	Option
	Multicom	All connectivities in one single device	Option	Option
Terminal connections	USB Type C	Host & Slave	●	●
Batteries	Li-ion	1200mAh (removable)	●	●
Terminal size	L x W x H L x W x H	129 x 70 x 17 mm (5.07 x 2.75 x 0.67) 129 x 70 x 18 mm (5.07 x 2.75 x 0.70)	●	●
Weight	Full featured	155g (5.46oz) 167g (5.89z)	●	●
Environment	Charging T°	0°C to +40°C (32°F to 104°F)	●	●
	Operating T°	-10°C to +50°C (14°F to 122°F)	●	●
	Storage temperature	-20 to +55°C (-4°F to 131°F)	●	●
	Relative humidity, non condensing	85% non-condensing at 40°C (104°F)	●	●
Power supply	Terminal	5V 1A	Option	Option
Accessories	Cable	USB A to USB C: 1.5m	●	●
Security		PCI PTS 4.x & v5.x online & offline certified	●	●



www.ingenico.com

