

Xplore DT433

The Xplore DT433 is a powerful and robust POS PDA that delivers superior features with proven reliability at an affordable price. Not only does the DT433 carry advanced features such as Single SSID Lock, Always On WiFi, Seamless WiFi Roaming, Configurable Roaming Trigger, Admin/User Modes, etc., but it also brings new features in power management, deployment, and maintenance to a whole new level.

The 4.3" sunlight readable LCD, together with the automatic screen brightness control, provides optimum viewing in a variety of environments. The integrated G-sensor enables the development of landscape or screen rotation applications with ease. To maximise battery operation hours, the automatic sleep activation (through flip cover closure) and the new dynamic power management system drives the power consumption to absolute minimum levels in both operation and unattended modes.

The DT433 is also built-in with the Xplore Remote Assistant utility that allows system integrators to provide instant and effective support for remote sites over the Internet. Software upgrade, user training, commissioning, troubleshooting etc. can be conducted efficiently without site visits; saving significant time and resource for ongoing customer support.

With IP54 certification and 1.5m drop specification, the feature-rich Xplore DT433 is designed for use in harsh operating environments, thus making the device an ideal choice for hospitality applications.



Features:

- Windows CE 5.0 with enhanced performance features at driver & UI levels
- 4.3" WQVGA Colour LCD with Touch Panel
- WiFi 802.11b/g, Bluetooth 2.0
- Single SSID lock, Always-on WiFi, Seamless roaming, Configurable roaming
- Admin/ User operation mode
- Auto LCD brightness control
- Auto LCD screen rotation
- Auto sleep mode by closing flip cover
- MicroSD card slot for memory expansion
- Support Remote Desktop Protocol with auto-logon
- Clone and restore utility for system back up and easy field deployment
- Built-in Xplore Remote Assistant utility to support remote management
- Built-in microphone enables intercom application development.
- Independently certified to meet IP54 standard
- Withstand multiple drops from 1.5m onto concrete

Technical specifications:

	DT433
CPU	ARM9 533MHz
Operating System	Windows CE 5.0 Professional Edition
Display	4.3" WQVGA TFT Colour LCD with Touch Panel
Memory	128MB DDR RAM
	128MB Flash
Memory Expansion	Micro-SD card slot
WLAN	IEEE 802.11b/g
WPAN	Bluetooth v2.0 with EDR
Sensor	Ambient Light Sensor G-Sensor
LED Indicator	Wireless/Power LED
Vibrator	Built-in Vibrator
Audio	Mono Speaker & Microphone
Keys	Power key, Configurable shortcut key, 5-Way Navigaton keys, Reset key
USB	Mini USB Connector USB 2.0
Battery	Standard 1800mAh
Battery Life	Operating Time - 9 hrs Standby Time - 90 hrs
Charging	Single Slot Charging Cradle
Environmental	IP54 Rating Withstand multiple drops from 1.5m onto concrete
Dimension (mm)	141.6 x 77.9 x 19.5
Weight	245g